## Sheet Vinyl Flooring TECHNICAL DATA SHEET

Characteristics	Unit	Standards	Specification
Total Thickness	mm	ISO 4593:1993	2.00
Wear Layer Thickness	mm	ISO 4592:1992	0.50
Length	m	ISO 4592:1992	10.0
Width	m	ISO 4592:1992	1.83
Mass (gsm)	g/m²	ISO 3801	3,500
Hardness Shore D	°A	ISO 7619:2010	>55
Gloss Value (Matt)	GU	ISO 2813:2014	5
Abrasion Resistance	mm³	ISO 4649:2010	Group T
Resistance to Chemicals		EN ISO 26987	1
Castor Chair Test		ISO 4918	ОК
Thermal Conductivity	W/mK	ASTM D3801	0.11 ± 0.03
Reaction to Fire		EN ISO 11925-2	Class Bf1-s1
Bacteria Resistance		ISO 846: Part C	Does Not Favour Growth

Vinyl sheet flooring comes in several attractive natural wood designs. As these are sheets, they are much easier to install compared to the planks and have effectively less seam edges resulting in a more durable floor. They are very easy to clean and maintain ensuring you of a clean and hygienic environment. It's an ideal flooring for cafés, restaurants, offices, supermarkets or even residences and a variety of other commercial customer environments. This is a heterogeneous Vinyl flooring with a very strong wear layer that gives the protection that is needed in high foot traffic area. The wood emboss gives it a more authentic look while also acting as slip resistance.











(+94) 77 298 4212



Manufactured & Marketed by

## **GLOBAL VINYL (PVT) LTD.**

www.facebook.com/globalvinyl

www.instagram.com/hetrofloorin