

WOOD PLANK SHEET FLOORING

Vinyl wood plank sheet flooring comes in attractive wood designs. As this are sheets, they have less seam edges compared to planks. They are very easy to clean and maintain in a hygienic environment. Ideal for residences, offices, supermarkets, cafes and a variety of other commercial customer environments. This is a heterogenous floor with a very strong wear layer that gives the protection that is needed in high traffic area. The wood emboss makes this slip resistance and provides it wit the authentic wood look.

- **Fire resistant**
- **Water proof**
- **High strength**
- **Moisture resistance**
- **Durability**
- **Chemical resistance**
- **100% recyclable**




LUXURY WOOD PLANK SHEET FLOORING



Structural view

Product is made up with three layers



- ① Wear layer
- ② Print design layer
- ③ Back layer

Color Range



Residences, Café, Showrooms, Offices, Restaurants, Indoor sports, Warehouses

Technical Specification

Characteristics	Unit	Test Method	Specification
Thickness	mm	ISO 4593:1993	2.00
Length	m	ISO 4592:1992	10.00
Width	Inch/cm	ISO 4592:1992	72/183
Mass(GSM)	g/m ²	ISO 2286	3650.00
Hardness Shore D	□ A	ISO 7619:20104	10
Abrasion Resistance	mm ²	ISO 4649:2010	292
Anti Static	MΩ/500V	ISO 2878:2005	>200MΩ
Flammability	class	ASTM D3801	V - 0
Thermal Conductivity	W/mK	ISO 22007:2008	0.11 ± 0.03
Abrasion Volume Loss	mm ³	EN 660: Part - 2	Group P: Š 4.0
Chemical Resistance		ISO 26987 - E 423	Good resistance
Bacteria Resistance		ISO 846: Part C	Does not favour growth
Castor Chair Test		ISO 4918 - EN 425	suitable

Installation

The condition of the subfloor is critical to the appearance of the finished installation and the life and serviceability of the floor covering. It is essential, therefore, that the subfloor be dry, hard, rigid, smooth, level, clean and free of dust and grease. A resin based membrane could be used as a moisture mitigation system as applicable. Our recommended adhesive should be used.

Maintenance & Cleaning

Remove dirt and dust from the floor using a dust mop. Residual stubborn dirt on the flooring can be removed using a wet mop with neutral detergent (such as "Diverse All Purpose Clear" or other similar products) Clean the flooring using a clean mop. Allow to dry & dry burnish the flooring using floor polisher.



Manufactured & Marketed by

GLOBAL VINYL (PVT) LTD.

Head Office

208, Sea Street,
Colombo 11, Sri Lanka.
T +94 11 2435006
F +94 11 2439656

Factory

431, 432, Makandura Industrial Estate,
Makanadura, Gonawila (NWP), Sri Lanka.
T +94 31 2298063
F +94 31 2298026

www.globalvinyl.lk

www.facebook.com/globalvinyl

LUCKY DISSANAYAKE GRAPHICS - 0777-942-537